

Material Safety Data Sheet

Issue Date: September 3, 2009
Page 1 of 4

Section I – Identification

Product Identification: Fire Resistant Cellulose Based Fiber Board**Product Name:** FireStall roof deck, FireStall Panels.**Product Use/application:** Building Material**Company:** Homasote Company
P.O. Box 7240
West Trenton, NJ, 08628-0240.**Contact Numbers:**

Toll Free: 800-257-9491 Ext. 1500. Telephone: 609-883-3300. Fax: 609-406-9263.

Website: www.homasote.com

Section II – Composition/Information on Ingredients

Cellulose based material containing 1 to 2% paraffin wax, CAS 8002-74-2, 20 to 25% aluminum trihydrate, CAS 21645-51-2, and less than 0.1% copper base pesticide, CAS 39290-85-2. The product contains no known hazardous or carcinogenic components.

Section III – Hazards Identification

Routes of Entry: skin contact, eye contact and inhalation of dust.**Health Effects****Inhalation:** nasal dryness and mild irritation.**Eye contact:** dryness and mild irritation.**Skin contact:** can cause minor irritation and dryness.

Section IV – First Aid Measures

Inhalation: Move the individual to a dust-free area. Seek medical attention if persistent coughing or difficult breathing develops.**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists.**Eye Contact:** Treat as a foreign object. Flush eyes with water.

Section V – Fire Fighting Measures

Material is fire retardant, but flammable, not explosive.

Extinguishing Media: Water, carbon dioxide (CO₂).**Special Risks:** Combustion produces irritating and toxic fumes and gases, including carbon monoxide (CO) and carbon dioxide (CO₂). Dust may explode at concentrations greater than 40 grams dust per cubic meter of air.**Special Protective Equipment:** Self contained breathing apparatus recommended.

Section VI – Accidental Release Measures

No health related procedures required. Avoid or control conditions that could result in fire.

Section VII – Handling and Storage

No health related procedures required. Avoid or control conditions that could result in fire.

Material Safety Data Sheet

Issue Date: September 3, 2009

Page 2 of 4

Section VIII – Exposure Controls/Personal Protection

Personal Protective Equipment: recommended for sanding, sawing, and other machining.

Respiratory Protection: dust mask and local exhaust.

Eye Protection: safety glasses.

Hand Protection: as required for mechanical operations.

Industrial Hygiene: Follow normal work hygiene practices. No special practices required.

Section IX – Physical and Chemical Properties

Form: solid board.

Odor: none.

Melting Point: na.

Ignition Temperature: 450 ° F.

Density: 30 to 34 lb/ft³.

Color: gray.

pH: na.

Boiling Point: na.

Flash Point: na.

Solubility in water: negligible.

Explosion Limit – Lower: 40 grams of dust per cubic meter air for cellulose dust.

Explosion Limit – Upper: unknown.

Section X – Stability and Reactivity

Conditions to be Avoided: Conditions that could cause ignition or fire.

Substance to be Avoided: none known.

Hazardous Decomposition Product(s): Burning produces irritating and toxic smoke and fumes including paraffin wax fumes, carbon monoxide, and carbon dioxide.

Section XI – Toxicological Information

no known toxicological effects

Section XII – Ecological Information

Significant ecotoxic effects are not expected.

Section XIII – Disposal Considerations

Dispose in accordance with local, state, federal, and provincial environmental regulations.

Section XIV – Transportation Information

Road/Rail: not regulated by DOT

Material Safety Data Sheet

Issue Date: September 3, 2009
Page 3 of 4

Section XV – Regulatory Information

CERCLA: This product does not contain any chemicals subject to reporting as a CERCLA hazardous substance under 40 CFR 302.4

EPCRA: This product does not contain any chemicals subject to reporting as a toxic chemical under EPCRA Section 313.

CIS R(isk) Phrases:

R 10: Flammable

R 43: May cause sensitization by skin contact

R 66: Repeated exposure may cause skin dryness or cracking

CIS S(afety) Phrases:

S 15: Keep away from heat

S 16: Keep away from sources of ignition

S 17: Keep away from combustible material

S 22: Do not breathe dust

S 38: In case of insufficient ventilation, wear suitable respiratory equipment

S 41: In case of fire, do not breathe fumes.

Section XVI – Other Information

HMIS Ratings:

Health 1 slight hazard

Flammability 0 minimal hazard

Reactivity 0 minimal hazard

Safety Officer Telephone No: 609-883-3300, X1188

Safety Officer Fax No: 609-530-1584

Safety Officer 24hr Telephone No: 609-883-3300

List of Acronyms

ACGIH American Conferences of Governmental Industrial Hygienists

CAS(RN) Chemical Abstracts (Registry Number)

CERCLA Comprehensive Emergency Response, Compensation, and Liability Act

CIS International Occupational Safety and Health Information Center

EPCRA Emergency Planning and Community Right-to-Know Act

HMIS Hazardous Materials Identification System

IARC International Agency for Research on Cancer

IDLH Immediately Dangerous to Life or Health (NIOSH)

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL OSHA Permissible Exposure Limit

TLV Threshold Limit Values (Registered Trademark of ACGIH)

TWA Time Weighted Average



*Sensible. Sound.
Solutions.*

Material Safety Data Sheet

Issue Date: September 3, 2009
Page 4 of 4

The information contained herein is based on the present state of our knowledge.
The information contained herein characterizes the product with regard to the appropriate safety precautions.
The information contained herein does not represent a guarantee of the properties of the product.