



DON'T SPOIL THE COIL

Protect your metal coils during stacking and shipping with CoilSafe.™ The easy way to prevent costly damage to edges of metal coil.

Dense CoilSafe material is more moisture-resistant than wood—even in damp environments. In fact, CoilSafe is excellent for overseas shipping*. Plus CoilSafe has a linen-like surface that grabs the load, minimizing slipping and shifting.

* Meets requirements for ISPM-15

HOMASOTE®


*Sensible. Sound.
Solutions.*

Pak-Line®
Registered trademark of
Homasote Company





www.homasote.com

CoilSafe™



CoilSafe separators in segmented strip form are shipped on 48" x 48" neatly stacked skids that can be placed close to banding lines for easy access as coils are being packed.

- Splinter-free handling
- Material grips the coil, reducing slippage
- Sap-free, will not damage or discolor metal
- Uniform in thickness for better stacking
- Pre-slit, snaps apart at desired length, no sawing required
- Moisture-resistant, drier than kiln-dried wood
- Recycled material reduces waste
- Eliminates damage to material
- Saves labor cost



Uniform in thickness, density and desired length, CoilSafe 4", 6", 8" or 12" segments, break apart easily for fast, splinter-free application.



CoilSafe™ Thickness			Per Skid
Inches	Decimal	MM	48" Strips
7/16"	.4375"	11mm	4032
5/8"	.6250"	16mm	2800
3/4"*	.7500"	19mm	2240
1"	1.000"	25mm	1680
1-1/2"	1.500"	38mm	1120
2"	2.000"	50mm	720
All skids weigh 2,400 lbs.			*HD substrate

All thickness are nominal

HOMASOTE® Sensible. Sound. Solutions.

Pak-Line®
Registered trademark of Homasote Company

800-257-9491 • Technical Support call Ext. 1332 or e-mail techhelp@homasote.com

www.homasote.com